

Inox pipes



Element straight 1000mm														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
	Usable height	940	940	940	940	940	940	940	940	940	940	940	940	940

Angle 45														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	110	115	118	120	122	125	130	130	135	140	140	145	155

Angle 90														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300

	Item Height	175	185	195	200	205	210	215	225	235	245	250	260	280
---	-------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Splitter 90														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	250	250	330	330	330	330	330	500	500	500	500	500	500
	Usable height	190	190	270	270	270	270	270	270	440	440	440	440	440
	Distance	140	155	160	165	170	175	180	190	200	210	215	225	250

Systolic Sign STR / STR														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	30
The diameter refers to the largest diameter. When ordering the smallest desired diameter should be disclosed														

Closing cap														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	100	100	100	100	100	100	100	100	100	100	100	100	100

Windproof head Chinese														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	340	340	340	340	340	340	340	340	340	340	360	360	360

Wall Bracket														
	Diameter	80	100	120	130	140	150	160	180	200	220	230	250	300
	Item Height	50	50	50	50	50	50	50	50	50	50	50	50	50

Insulated Inox pipes



Element straight (1000mm)									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350
	Item Height	1000	1000	1000	1000	1000	1000	1000	1000
	Usable Height	940	940	940	940	940	940	940	940
	Item Thickness	25	25	25	25	25	25	25	25

Angle 30									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350

	Item Height	110	115	119	120	125	130	135	140
	Item Thickness	25	25	25	25	25	25	25	25

Angle 45									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350
	Item Height	120	125	130	135	140	145	155	165
	Item Thickness	25	25	25	25	25	25	25	25

Angle 90									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350
	Item Height	200	210	225	235	250	260	285	310
	Item Thickness	25	25	25	25	25	25	25	25

Splitter 90									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350
	Item Height	500	500	500	500	500	500	500	550
	Usable Height	440	440	440	440	440	440	440	440
	Item Thickness	25	25	25	25	25	25	25	25
	Distance	165	175	190	200	215	225	250	275

Systolic Sign STR / STR									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350
	Diameter	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350	350 - 400
	Item Thickness	25	25	25	25	25	25	25	25

Windproof head Chinese									
	Diameter	80 - 130	100 - 150	130 - 180	150 - 200	180 - 230	200 - 250	250 - 300	300 - 350

	Item Height	340	340	340	340	340	340	360	360
	Item Thickness	25	25	25	25	25	25	25	25

Wall Bracket									
	Diameter	130	150	180	200	230	250	300	350
	Height Base	50	50	50	50	50	50	50	50